

DECLARATION OF PERFORMANCE
No. CPR_01

1. Unique identification code of the product type : **Dry-pressed ceramic tiles, with water absorption $E_v \leq 0,5 \%$**
2. Intended uses: **For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer: **Ceramiche Marca Corona, via Emilia Romagna, 7 – 41049 Sassuolo (MO) ITALY**
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411 : 2012
Release of dangerous substance		
- Cadmium	npd	
- Lead	npd	
Breaking strength (thickness $\geq 7,5$)	≥ 1300 N	
Breaking strength (thickness $< 7,5$)	≥ 700 N	
Slipperiness	See table attached	
Tactility	npd	
Bond strength/adhesion	npd	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

Table - Slipperiness (where required by regulation) - rev.1_ 27/08/2018 – ARKISTONE

Serie	Product	DIN 51130 (DE)	B.C.R.A. D.M.236/1989 (ITA)	Basic document SU 3/2006 (ESP)	Others....
ARKISTONE	Ivory	R10	> 0,40	NPD
	Light				
	Greige				
	Silver				
	Dark				
	Ivory Trama	R10	> 0,40	NPD
	Light Trama				
	Greige Trama				
	Silver Trama				
	Dark Trama				
	Ivory Strutt.	R11	> 0,40	NPD
	Light Strutt._ Light Strutt. SP 2 cm				
	Greige Strutt.				
	Silver Strutt._ Silver Strutt.SP 2 cm				
	Dark Strutt._Dark Strutt.SP 2 cm				

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
Signed for and on behalf of the manufacturer by:

Sassuolo,

Lelio Poncemi_CEO